

Infiniti RIGID CORE LVT Parchment



Parchment

Infiniti Quick-Ship Collection by terra legno

SPECIFICATIONS

Classification: ASTM F-3261-17 Resilient flooring in modular format with Rigid Polymeric Core Size: 7" x 60" x 5.5 mm (0.21") SPC Core Standard Dimensions: 4.mm Commercial Wear Layer: 0.5mm / 20mil Wear Layer Top-Coat Finish: Polyurethane with **Ceramic Beads** Standard Backings: IXPE Foam1.5mm Edge: Square Edge Colors: 12 Standard Colors Embossed: Yes Pattern Repeat: 5.67 Installation: Unilin 2G Angle / Tap Moldings: SlimTrim 3-in-1 & Versa Edge Packaging: 29.52 S/F Cartons, 10 Planks per Ctn. Pallet 55 Ctns. Dimensional Stability: ASTM F2199 - PASSED Heat Stability: ASTM 1514 - PASSED Light Stability: ASTM 1515 - PASSED Residual Indentation: ASTM F1914 - PASSED Static Load: ASTM F970 - PASSED Stain Resistance: ASTM F925 - PASSED Slip Resistance (Static Coefficient of Friction): ≥ 0.5 Fire Performance (Critical Radiant Flux): ASTM E648 – CLASS 1, ≥ 0.45 **Impact Sound Testing:** IICc-28 ΔIIC = 23db **STC Sound Testing:** ASTM E 90-2009 (R2016) – STC 62 IIC Sound Testing: ASTM E 492-09 (2016)ε1 – IIC 65

INSTALLATION

Methods: Float and Glue Down

Areas: On Grade, Below Grade & Above Grade

CARE & MAINTENANCE

For current floor care and maintenance guidelines please visit <u>www.terralegno.com</u> or contact Terra Legno, Ltd. at 800-973-7424

WARRANTIES

Lifetime Limited Structure Lifetime Limited Waterproof Lifetime Limited Petproof Lifetime Limited Residential Wear 30 Year Limited Commercial Wear



CERTIFICATIONS

Phthalate Free FloorScore ISO 9001

CONTACT & SAMPLES

For further information and sample requests: www.terralegno.com info@terralegno.com P: 800-393-7424

