

ш \bigcirc LT L Ζ LL \triangleleft \geq \square \bigcirc ш α α ш \cap шΟ сц ш \square ш Ш Z \square 0 Ш ш Z Ζ ш C \geq ш

Ebony Spectrum Collection "Custom Grafted, Custom Made"

Prefinished Engineered Flooring Wide Plank, Herringbone & Chevron Plain Sawn, Rift & Quarter, Rift & Live Sawn



Ebony

SPECIFICATIONS

Species: Northern White Oak, Northern Red Oak, Northern Hard Maple, Northern Hickory, Northern American Walnut

Janka Hardness: White Oak 1360, Red Oak 1290, Maple 1450, Hickory 1820, American Walnut 1010

Wood Cut Options: Plain Sawn & Live Sawn All Species

Grade: Select & Character

Wood Cut Options White Oak & Red Oak:

Plain Sawn, Live Sawn, Quarter Sawn, Rift Sawn, Rift & Quarter Sawn

Wear Layer: 4mm Sawn Faced

Style: Single Planks, Herringbone, Chevron, & Architectural Parquet Patterns.

Plank Widths: 1.5"-12"

Dimensions: Engineered Construction: $5/8 \& 3/4'' \times 1.5$ -12" x 2- 10' RL / Avg. Board Length 5'+ (Based on Availability to 2' - 14' RL)

Solid Construction: ³/₄" x 1.5" – 9" x 1'-9' RL ABL 5'+

Herringbone & Chevron Patterns:

W x 30", 36", 40" & Custom Made to Specifications

Parquet Patterns: Made to Specifications

Engineered Core Construction: 5/8" & 3/4" Baltic Birch Multi-ply

Finish: UV-Polyurethane and UV-Oil

Finish Texture Options: Smooth, Wire Brushed, Hand

Scraped, Saw-Mill Cuts, Burnt, French Bleed

Stains: Custom Color Matching Available

Prefinished Edge: Micro-Bevel , Full Bevel, Scraped

Unfinished Edges: Straight Edge & Micro Bevel


Moldings: Reducer, Stair Nose, Baby Threshold, T-Mold, Heat

Vents, Stair Treads & Risers

Custom Made to Order Moldings Available




StairMax Stairnose:



Shade Variance: Natural products like wood flooring have inherent color & shade variations. The degree of variation is related to the species and the grading.

Light Sensitivity: Wood Species have their unique level of sensitivity to light and color change.



Solid Hardwood = 4mm Wear Layer

terra legno Engineered Flooring offers the exact look and refinishing features of solid wood flooring with superior dimensional stability and performance of engineered construction.

INSTALLATION

Methods: Staple / Nail Down, & Glue Assist, Glue & Nail Down, Glue Down, Staple / Nail, Float **Areas:** On Grade, Below Grade & Above Grade

For best results, wood floors installed by a wood flooring professional equal to an NWFA Certified Installer. Up to date installation guidelines available at: www.terralegno.com.

CARE & MAINTENANCE

Residential and Commercial Wood Flooring Maintence with NeoTech Polyurethane Finish. Floor Care and Maintenance details refer to <u>www.terralegno.com</u>

WARRANTIES

Lifetime Structural Warranty 35 Year Residential Finish Warranty 5 Year Light Commercial Finish Warranty 3 Year Commercial Finish Warranty



CERTIFICATIONS

CARB 2 Compliant Lacey Act LEED Potential Credits

CONTACT & SAMPLES

For further information and sample requests: www.terralegno.com info@terralegno.com P: 800-393-7424