







Hearthstone

Autentico Collection

European White Oak Sliced Prefinished Engineered Flooring Wide Plank, Herringbone & Chevron







HEARTHSTONE

SPECIFICATIONS

Species: European White Oak

Janka Hardness: 1360 Grading: Select Prime Wear Layer: 2mm Sliced Style: Single Planks Thickness: 1/2" Width: 6-1/2"

Length: 60%+ 61/4' 40% 18" - 48"

Chevron & Herringbone Dimension: Custom Made to

Specifications

Finish: NeoTech UV-Polyurethane with Aluminum Oxide

Stains & Treatments: Wire Brushed, Stained **Prefinished Edge:** Micro-Bevel 4 Sided

Core Construction: Multi-ply

ADDITIONAL OPTIONS

Moldings: Standard Flush Mount & Overlap Moldings, Heat Vents, Stair Treads & Risers, Custom Made to Order Moldings Available.



Stair Treads & Risers: 36", 42", 48", 60" 72"

Heat Vents with Dampers: Drop-In and Flush Mount


StairMax Stairnose:



Shade Variance: Natural products like wood flooring have inherent color & shade variations. The degree of variation is related to the species and the grading.

Light Sensitivity: Wood flooring is light sensitive. Over time, the color of wood naturally changes when exposed to light. Natural UV light and direct sunlight results in the greatest amount of change. The lighting in the room can affect the color of the wood floor.

Reactive Stains & Light Sensitivity: Wood species with higher tannins, like European White Oak, finished with Reactive Stains inherently have a higher sensitivity to light and color change.





Solid Hardwood = 4mm Wear Layer

terra legno Engineered Flooring offers the exact look and refinishing features of solid wood flooring with superior dimensional stability and performance of engineered construction.

INSTALLATION

Methods: Staple Nail & Glue Assist, Staple / Nail & Glue Down, Glue Down, Floating, Nail Down Installation

Areas: On Grade, Below Grade & Above Grade

For best results, wood floors installed by a wood flooring Professional equal to an NWFA Certified Installer

CARE & MAINTENANCE

Residential and Commercial Wood Flooring Maintence with NeoTech Polyurethane Finish. Floor Care and Maintenance details refer to www.terralegno.com

WARRANTIES

Lifetime Structural Warranty 35 Year Residential Finish Warranty 5 Year Light Commercial Finish Warranty 3 Year Commercial Finish Warranty



CERTIFICATIONS

CARB 2 Compliant FSC on Request Lacey Act LEED Potential Credits

CONTACT & SAMPLES

For further information and sample requests: www.terralegno.com info@terralegno.com
P: 800-393-7424