

ШΟ

Taupe

Spectrum Collection "Custom Crafted, Custom Made"

Prefinished Engineered Flooring Wide Plank, Herringbone & Chevron Plain Sawn, Rift & Quarter, Rift & Live Sawn





TAUPE

SPECIFICATIONS

Species: Northern White Oak, Northern Red Oak,

Northern Hard Maple, Northern Hickory,

Northern American Walnut

Janka Hardness: White Oak 1360, Red Oak 1290, Maple1450, Hickory 1820, American Walnut 1010

Wood Cut Options: Plain Sawn & Live Sawn All Species

Grade: Select & Character

Wood Cut Options White Oak & Red Oak:

Plain Sawn, Live Sawn, Quarter Sawn, Rift Sawn, Rift &

Quarter Sawn

Wear Layer: 4mm Sawn Faced

Style: Single Planks, Herringbone, Chevron, & Architectural

Parquet Patterns.

Plank Widths: 1.5"-12"

Dimensions: Engineered Construction: $5/8 \& 3/4" \times 1.5$ $-12" \times 2-10' RL / Avg.$ Board Length 5'+ (Based on Availability to 2'-14' RL)

Solid Construction: 3/4" x 1.5" – 9" x 1'-9' RL ABL 5'+

Herringbone & Chevron Patterns:

W x 30", 36", 40" & Custom Made to Specifications

Parquet Patterns: Made to Specifications

Engineered Core Construction: 5/8" & 3/4" Baltic Birch Multi-ply

Finish: UV-Polyurethane and UV-Oil

Finish Texture Options: Smooth, Wire Brushed, Hand

Scraped, Saw-Mill Cuts, Burnt, French Bleed **Stains:** Custom Color Matching Available

Prefinished Edge: Micro-Bevel , Full Bevel, Scraped **Unfinished Edges:** Straight Edge & Micro Bevel


Moldings: Reducer, Stair Nose, Baby Threshold, T-Mold, Heat

Vents, Stair Treads & Risers

Custom Made to Order Moldings Available





StairMax Stairnose:



Shade Variance: Natural products like wood flooring have inherent color & shade variations. The degree of variation is related to the species and the grading.

Light Sensitivity: Wood Species have their unique level of sensitivity to light and color change.





Solid Hardwood = 4mm Wear Layer

terra legno Engineered Flooring offers the exact look and refinishing features of solid wood flooring with superior dimensional stability and performance of engineered construction.

INSTALLATION

Methods: Staple / Nail Down, & Glue Assist, Glue & Nail

Down, Glue Down, Staple / Nail, Float

Areas: On Grade, Below Grade & Above Grade

For best results, wood floors installed by a wood flooring professional equal to an NWFA Certified Installer. Up to date installation guidelines available at: www.terralegno.com.

CARE & MAINTENANCE

Residential and Commercial Wood Flooring Maintence with NeoTech Polyurethane Finish. Floor Care and Maintenance details refer to www.terralegno.com

WARRANTIES

Lifetime Structural Warranty
35 Year Residential Finish Warranty
5 Year Light Commercial Finish Warranty
3 Year Commercial Finish Warranty



CERTIFICATIONS

CARB 2 Compliant Lacey Act LEED Potential Credits

CONTACT & SAMPLES

For further information and sample requests: www.terralegno.com info@terralegno.com P: 800-393-7424