



Walnut Rustic

Neuvo Classico Collection

North American Walnut Saw Cut Prefinished Engineered Flooring Wide Plank, Herringbone & Chevron











WALNUT RUSTIC

SPECIFICATIONS

Species: North American Walnut

Janka Hardness: 1010

Cut: Saw Cut Grade: Mixed Select Thickness: 9/16"

Width: 6"

Length: 35%+6¼′ 65% RI Wear Layer: 3 mm Sawn Faced

Herringbone Dimension: 9/16" X 6" X 36" (Double

Grooved)

Chevron Dimension: 9/16" X 6" X 30" (Double Grooved)

Other Custom Sizes Available

Finish: Neotech UV-Polyurethane With Aluminum Oxide

Stains & Treatments: Wire Brush, Stain

Edges: Micro-Bevel 4-Sided
Core Construction: Multi-Ply
ADDITIONAL OPTIONS

Moldings: standard flush mount & overlap moldings, custom

made to order moldings available



Stair treads & risers: 36", 42", 48", 60", 72"

Heat vents with damper: drop-in and flush mount


SHADE VARIATION & COLOR CHANGE




Shade Variance: Natural products like wood flooring have inherent color & shade variations. The degree of variation is related to the species and the grading.

Light Sensitivity: Wood flooring is light sensitive. Over time, the color of wood naturally changes when exposed to light. Natural UV light and direct sunlight results in the greatest amount of change. The lighting in the room can affect the color of the wood floor.

Reactive Stains & Light Sensitivity: Wood species with higher tannins, like European White Oak, finished with Reactive Stains inherently have a higher sensitivity to light and color change.





Solid Hardwood = 4mm Wear Layer

terra legno Engineered Flooring offers the exact look and refinishing features of solid wood flooring with superior dimensional stability and performance of engineered construction.

INSTALLATION

Methods: Staple/ nail down & glue assist, glue & staple/ nail down, glue down, staple & nail down, or float

Areas: On grade, below grade & above grade

For best results, wood floors installed by a wood flooring Professional equal to an NWFA Certified Installer.

CARE & MAINTENANCE

Residential and Commercial Wood Flooring Maintence with NeoTech Polyurethane Finish. Floor Care and Maintenance details refer to www.terralegno.com

WARRANTIES

Lifetime Structural Warranty
35 Year Residential Finish Warranty
5 Year Light Commercial Finish Warranty
3 Year Commercial Finish Warranty



CERTIFICATIONS

CARB 2 Compliant
FSC on Request
Lacey Act
LEED Potential Credits

CONTACT & SAMPLES

For further information and sample requests: www.terralegno.com info@terralegno.com
P: 800-393-7424